

A152

STUDIO REFERENCE HEADPHONES WITH EXTENDED BASS

OVERVIEW

With an extremely wide sound field and the most extended bass response, the A152 headphones represent a new level of sound reproduction for audiophile listeners. Studio or hi-fidelity listening alike, the A152 captures every detail and nuance in the sound field. Even gaming enthusiasts using the A152 headphones will enjoy an audible advantage, when split seconds matter. The full range 50 mm phase coherent drivers coupled with the lightweight and comfortable headset design, provide hours of listening without fatigue.

FEATURES

- Dynamic, closed back design
- Excellent for audio playback and monitoring
- Over-the-ear design built for comfort and isolation
- Soft cushion ear cups with 90-degree swivel for easy single-ear monitoring
- High-performance, phase coherent drivers
- Ultra wide sound field
- Deep, accurate bass
- Accurate reproduction of subharmonics
- Two detachable cables: 3.0 m (9.8') for studio, 1.8 m (6') for travel

SUPPLIED ACCESSORIES

- **CBLHP96** Headphone Cable - Detachable 1.8 m high density, 3 conductor - 96 strands of braided OFC with 3.5 mm stereo plug
- **CBLHP96XL** Headphone Cable - Detachable 3.0 m high density, 3 conductor - 96 strands of braided OFC, with soft nylon woven jacket with 3.5 mm stereo mini plug
- **CBLADPT** 3.5 mm (1/8 in) mini to 6.3 mm (1/4 in) threaded adapter
- **POUCHHP** Protective carrying case

OPTIONAL ACCESSORIES

- **CBLHP400** Audiophile Pro Headphone Cable - Detachable 1.5 m high density, 3 conductor - 400 strands of 8 core braided OFC with 3.5 mm stereo plug
- **CBLHPEXT** Headphone Extension Cable - Detachable 1.5 M high density, 3 conductor - 96 strands of braided OFC with 3.5 mm stereo female and male connectors

MODEL VARIATIONS

- **A140** - Professional studio headphones
- **A145** - Professional studio headphones with extended bass
- **A150** - Studio reference headphones



SPECIFICATIONS

Operating Principle	Dynamic
Driver Size	50 mm
Magnet	Rare Earth Alloy
Sensitivity (@ 1 kHz)	103 dB (± 3 dB)
Impedance	30 Ohm
Frequency Range	8 Hz - 28 kHz
Connector	3.5 mm (1/8 in) stereo plug
Cables	1.8 m detachable high density 3 conductor - 96 strands of braided silver coated oxygen free copper 3.0 m detachable high density 3 conductor - 96 strands of braided silver coated oxygen free copper